



**APC Smart-UPS C 1000VA LCD 230V**  
**Part Number: SMC1000I**



[Technical Specifications](#)   [Product Overview](#)   [Documentation](#)   [Software & Firmware](#)   [Options](#)   [Ratings and Reviews](#)

**Output**

Output Power Capacity	600 Watts / 1000 VA
Max Configurable Power	600 Watts / 1000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Topology	Line Interactive
Waveform Type	Sine wave
Output Connections	(8) IEC 320 C13  (2) IEC Jumpers

**Input**

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	180 - 287V
Input voltage adjustable range for mains operation	170 - 300V


**Batteries & Runtime**

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
--------------	--

Typical recharge time 3 hour(s)

RBC™ Quantity 1

### Runtime Graph



*Hover over the line on the graph above to view the runtime at any desired load*


Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.

[View Enlarged Graph](#)

[View Runtime Chart](#)

### Energy Use/Efficiency

Load	Efficiency
25%	93.5%
50%	96.2%
75%	96.9%
100%	97.2%



*Hover over the line on the graph above to view the efficiency at any desired load*

Curve fit to measured efficiency data. All measurements taken in normal operating mode, at typical environmental conditions, with nominal electrical input and balanced resistive load (PF = 1.0) output.

[View Enlarged Graph](#)

## Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	--

## Surge Protection and Filtering

Surge energy rating	455 Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	215.00 mm
Maximum Width	171.00 mm
Maximum Depth	439.00 mm
Net Weight	17.27 KG
Shipping Weight	19.55 KG
Shipping Height	376.00 mm
Shipping Width	328.00 mm
Shipping Depth	595.00 mm
Master Carton Units	1.00
Color	Black
Units per Pallet	18.00

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	41.00 dBA
Online Thermal Dissipation	100.00 BTU/hr

## Conformance

Regulatory Approvals	CE, GOST, VDE
Standard Warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.