

Share:







APC Smart-UPS 2200VA USB & Serial RM 2U 230V

SUA2200RMI2U



Description: Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Includes : CD with software , Rack Mounting Brackets , Smart UPS signalling RS-232 cable , USB cable , User Manual

Product Overview

Technical Specifications

Documentation

Software & Firmware

Options

Output

Print Technical Specification

Life is On



Output power capacity	1.98 KWatts / 2.2 kVA
Max Configurable Power (Watts)	1.98 KWatts / 2.2 kVA
Nominal Output Voltage	230V
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(8) IEC 320 C13 (Battery Backup) (1) IEC 320 C19 (Battery Backup) (2) IEC Jumpers (Battery Backup)
Transfer Time	2ms typical

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20, Schuko CEE 7 / EU1-16P, British BS1363A
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for mains operation	151 - 302V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	RBC43
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	480Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	89mm , 8.9cm
Maximum Width	483mm , 48.3cm
Maximum Depth	660mm , 66.0cm
Rack Height	2U
Net Weight	43.64kg
Shipping weight	51.5kg
Shipping Height	260mm , 26.0cm
Shipping Width	600mm , 60.0cm
Shipping Depth	980mm , 98.0cm
Color	Black
Master Carton Units	1.0
Units per Pallet	8.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	47.0dBA
Online thermal dissipation	300.0BTU/hr

Conformance

Approvals	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE
Standard warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Other Environmental Compliance	China RoHS

Sign up to stay up to date with best practices, new solutions and special offers.

Life is On | **Schneider**
Electric

Email

OK

CONNECT WITH US**FIND A RESELLER**

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO

[TERMS & CONDITIONS](#) >[PRIVACY STATEMENT](#) >

© 2017, APC by Schneider Electric