

Share:   



APC Smart-UPS C 3000VA LCD 230V

SMC3000I



Description: Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Includes : CD with software , Documentation CD , USB cable

Product Overview

Technical Specifications

Documentation

Options

Output

Print Technical Specification 

Output power capacity	2.1 KWatts / 3.0 kVA
Max Configurable Power (Watts)	2.1 KWatts / 3.0 kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	50 Hz
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(8) IEC 320 C13 (Battery Backup) (1) IEC 320 C19 (Battery Backup)

Input

Nominal Input Voltage	230V
Input frequency	47 - 63 Hz
Input Connections	IEC-320 C20
Input voltage range for main operations	180 - 287V
Input voltage adjustable range for mains operation	170 - 300V
Other Input Voltages	220, 240

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	APCRBC150
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console

Surge Protection and Filtering

Surge energy rating	300Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	435mm , 43.5cm
Maximum Width	197mm , 19.7cm
Maximum Depth	544mm , 54.4cm
Net Weight	43.0kg
Shipping weight	51.0kg
Shipping Height	762mm , 76.2cm
Shipping Width	381mm , 38.1cm
Shipping Depth	699mm , 69.9cm
Color	Black
Units per Pallet	24.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	45.0dBA
Online thermal dissipation	135.0BTU/hr

Conformance

Approvals	C-tick, CE, GOST, SABS, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

Sign up to stay up to date with best practices, new solutions and special offers.

Life is On |  Schneider Electric

Email

OK

WHO WE ARE

CONNECT WITH US

FIND A RESELLER

Enter Key Code

GO



[TERMS & CONDITIONS](#) >

[PRIVACY STATEMENT](#) >

© 2016, APC by Schneider Electric