





Share:








APC Smart-UPS C 3000VA Rack mount LCD 230V

SMC3000RMI2U



Description: Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Includes : CD with software , Documentation CD , Installation guide , Rack Mounting brackets , USB cable



Product Overview

Technical Specifications

Documentation

Software & Firmware

Options

Output

Print Technical Specification

Output power capacity	2.1 KWatts / 3.0 kVA
Max Configurable Power (Watts)	2.1 KWatts / 3.0 kVA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output frequency (sync to mains)	50 Hz
Topology	Line Interactive
Waveform type	Sine wave
Output Connections	(2) IEC Jumpers (Battery Backup) (1) IEC 320 C19 (Battery Backup) (8) IEC 320 C13 (Battery Backup)
Transfer Time	8ms typical : 10 ms maximum

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C20
Input voltage range for main operations	180 - 287V
Number of Power Cords	1

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	APCRBC151
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Runtime	<div>View Runtime Graph</div> <div>View Runtime Chart</div>

Communications & Management

Interface Port(s)	USB
Control panel	Multi-function LCD status and control console

## Surge Protection and Filtering

Surge energy rating	300Joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Physical

Maximum Height	89mm , 8.9cm
Maximum Width	480mm , 48.0cm
Maximum Depth	670mm , 67.0cm
Rack Height	2U
Net Weight	41.0kg
Shipping weight	50.9kg
Shipping Height	254mm , 25.4cm
Shipping Width	600mm , 60.0cm
Shipping Depth	980mm , 98.0cm
Color	Black
Units per Pallet	16.0

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	42.0dBA
Online thermal dissipation	81.0BTU/hr

## Conformance

Approvals	C-tick, CE, EAC, GOST, GS Mark, IRAM, SABS, VDE
Equipment protection policy	Lifetime : \$150000
Standard warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs



Sign up to stay up to date with best practices, new solutions and special offers.

Email

OK

WHO WE ARE

CONNECT WITH US

---

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO

---



[TERMS & CONDITIONS](#) >

[PRIVACY STATEMENT](#) >

© 2016, APC by Schneider Electric