

Share:   





APC Smart-UPS SRT 10000VA 230V

SRT10KXLI



Description: High density, double-conversion on-line power protection with scalable runtime

Includes : CD with software , Documentation CD , Installation guide , Temperature Probe , USB cable , Warranty card , Web/SNMP Management Card

Product Overview		Technical Specifications	Documentation	Drawings	Software & Firmware	Options
Output		Print Technical Specification 				
Output power capacity		10.0 KWatts / 10.0 kVA				
Max. Configurable Power (Watts)		10.0 KWatts / 10.0 kVA				
Nominal Output Voltage		230V				
Output Voltage Distortion		Less than 2%				
Output Frequency (sync to mains)		50/60Hz +/- 3 Hz				
Other Output Voltages		220, 240				
Load Crest Factor		3 : 1				
Topology		Double Conversion Online				
Waveform type		Sine wave				
Output Connections		(6) IEC 320 C13 (Battery Backup) (4) IEC 320 C19 (Battery Backup) (1) Hard Wire 3-wire (H N + G) (Battery Backup) (3) IEC Jumpers (Battery Backup)				
Bypass		Internal Bypass (Automatic and Manual)				
Input						
Nominal Input Voltage		230V , 400V 3PH				
Input frequency		40 - 70 Hz (auto sensing)				
Input Connections		Hard Wire 3 wire (1PH+N+G), Hard Wire 5-wire (3PH + N + G)				
Input voltage range for main operations		160 - 275V				
Input voltage adjustable range for mains operation		100 - 275 (half load), 173 - 476 (half load)V				
Other Input Voltages		220, 240, 380, 415				
Batteries & Runtime						
Battery type		Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof				
Typical recharge time		1.5hour(s)				
Replacement Battery		APCRBC140				
Expected Battery Life (years)		3 - 5				
RBC Quantity		2				

Runtime	View Runtime Graph	View Runtime Chart
Efficiency	View Efficiency Graph	

Communications & Management

Interface Port(s)	RJ-45 10/100 Base-T , RJ-45 Serial , Smart-Slot , USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	480Joules
---------------------	-----------

Physical

Maximum Height	432mm , 43.2cm
Maximum Width	263mm , 26.3cm
Maximum Depth	715mm , 71.5cm
Net Weight	111.82kg
Shipping weight	126.82kg
Shipping Height	461mm , 46.1cm
Shipping Width	600mm , 60.0cm
Shipping Depth	1000mm , 100.0cm
Color	Black

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95% non-condensing %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	1947.0BTU/hr
Protection Class	IP 20

Conformance

Approvals	CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, ENERGY STAR V1.0 (EU), IRAM, RCM, VDE
Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Battery Notes	ts_Battery_Notes

Email

OK

WHO WE ARE

CONNECT WITH US

FIND A RESELLER

Zip/Postal Code

FIND

CATALOG KEYCODE

Enter Key Code

GO



TERMS & CONDITIONS >

PRIVACY STATEMENT >

© 2016, APC by Schneider Electric