



> PRINT > COPY > SCAN > FAX

**TASKalfa 8052ci**

COLOUR MULTIFUNCTIONAL  
FOR A3 FORMAT

**COLOUR, BETTER,  
FASTER, STRONGER.**



All the best KYOCERA has to offer comes together in this uncompromising MFP. With a print speed of up to 80 A4 pages per minute for b/w and 70 for colour, a new colour technology that offers truly outstanding and vivid results and a maximum paper capacity of 7,650 sheets, it is not hard to see why this is the top model of our new TASKalfa series. And there's more: The TASKalfa 8052ci's fast performance is secured by an 8 GB Solid State Drive and a 320 GB HDD, enabling it to hold its high print speeds even at maximum print resolution. If you still need more icing on the cake, there's our optional Fiery Controller, which further refines both colour quality and productivity.

- > Up to 80 A4 ppm in b/w, up to 70 A4 ppm in colour
- > Outstanding image quality due to advanced colour technology
- > Standard print resolution of 1,200 x 1,200 dpi, 2 bit depth (equivalent of 4,800 x 1,200 dpi)
- > State-of-the-art 4.5 GB RAM + 8 GB SSD + 320 GB HDD
- > Long-life components reduce waste and provide exceptional efficiency and reliability
- > Individual paper handling options, including booklet and tri-folding
- > Optional Fiery Controller for highest productivity and colour quality



The TASKalfa 8052ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 8052ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

## TASKalfa 8052ci GENERAL

### Technology

KYOCERA Laser Colour, HyPAS™ solution platform

**Engine speed (pages per minute):** Up to 70/35 A4/A3 in colour, up to 80/40 A4/A3 in b/w

**Resolution:** 1,200 x 1,200 dpi, 2-bit depth for print quality of 4,800 dpi equivalent x 1,200 dpi

**Warm-up time from power on:** Approx. 44 seconds or less  
**Time to first page:** Approx. 4.8 sec. or less in b/w; 5.9 sec. or less in colour

**CPU:** Freescale QorIQ T1042 Quad Core 1.2 GHz

**Memory:** 4.5 GB RAM + 8 GB SSD + 320 GB HDD

**Standard interfaces:** USB 2.0 (Hi-speed) x4, USB Host 2.0, Fast Ethernet 10BaseT/100BaseTX/1000BaseT, slot for optional print server, slot for optional SD, SDHC card, slot for optional fax system

### Dimensions (W x D x H) – main unit

750 x 822 x 1234 mm (Include DP and Operation Panel)

**Weight:** Main unit approx. 182 kg

**Power source:** AC 220 V – 240 V, 50/60 Hz

### Power consumption

Printing: 1,360 W (in colour), 1,310 W (in b/w)

Ready mode: 120 W

Sleep mode: 1 W or less

### Noise (sound pressure level ISO 7779/ISO 9296)

Printing: 54.7 dB(A) LpA (in color), 54.1 dB(A) LpA (in b/w)

Ready mode: 34.9 dB(A) LpA

**Safety standards:** GS, TÜV, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHS compatibility

## PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

**Input capacity:** 150-sheet multi-purpose tray, 60 – 300 g/m<sup>2</sup> (banner 135 – 165 g/m<sup>2</sup>), A6R – 305 x 457 mm, banner max. 305 x 1,220 mm; 2x 1,500-sheet high-capacity paper deck, 60 – 256 g/m<sup>2</sup>, A4, B5; 2x 500-sheet universal paper cassette, 60 – 256 g/m<sup>2</sup>, A5R – 305 x 457 mm incl. custom paper sizes

Max. input capacity with options: 7,650 sheets A4

**Document processor:** (one-path duplex scanning) 270 sheets; 35 – 220 g/m<sup>2</sup> (simplex), 50 – 220 g/m<sup>2</sup> (duplex); A6R – Banner up to 2,200 mm

**Duplex unit:** Duplex as standard supports A5R – 305 x 457 mm, 60 – 256 g/m<sup>2</sup>

**Output capacity:** Standard job separator tray 70 sheets, optional copy tray (D): upper 100 sheets, lower 250 sheets  
Max. optional output capacity 4,300 sheets

## PRINT FUNCTIONS

**Controller language:** PRESCRIBE

**Emulations:** PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS

**Operating systems:** All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX, as well as other operating systems on request.

**Fonts/barcodes:** 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

**Print features:** Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, Private Print, job storage and job management functionality

**Mobile printing support:** KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google Cloud Print

## COPY FUNCTIONS

**Max. original size:** A3

**Continuous copying:** 1 – 9999

**Zoom range:** 25 – 400% in 1% steps

**Preset magnification ratios:** 5R/5E

**Digital features:** Scan once copy many, electronic sort, 2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page function.

**Exposure mode:** Auto, manual: 16 steps

**Image adjustments:** Text + photo, text, photo, map

## SCAN FUNCTIONS

**Functionality:** Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan

**Scan speed:** (A4, 300 dpi, Dual Scan) 220 images per minute

**Scan resolution:** 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit)

**Max. scan size:** A3, Banner up to 2,200 mm

**Original recognition:** Text, photo, text + photo, optimised for OCR

**File types:** PDF (high compression, encrypted, PDF/A), Searchable PDF (OCR), JPEG, TIFF, XPS, OpenXPS

## FAX FUNCTIONS (OPTIONAL)

**Compatibility:** ITU-T Super G3

**Modem speed:** Max. 33.6 kbps

**Transmission speed:** Max. 3 seconds (JBIG)

### Fax resolution:

Normal: 200 x 100 dpi

Fine: 200 x 200 dpi

Superfine: 200 x 400 dpi

Ultrafine: 400 x 400 dpi

600 x 600 dpi

**Maximum original size:** A3, Banner up to 1,600 mm

**Compression method:** JBIG, MMR, MR, MH

**Features:** Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system 12

## CONSUMABLES

**TK-8725K Toner-Kit:** Toner Black for 70,000 pages

**TK-8725C, TK-8725M, TK-8725Y Toner-Kits:**

Toner cyan, magenta, yellow for 30,000 pages Average continuous toner yield in accordance with 5% coverage A4.

**WT-861 Waste Toner Bottle:** 150,000 sheets (in accordance with 5% coverage. Colour: b/w = 6:4)

**Staple cartridge:** SH-10 for BF-730, SH-12 for DF-7110

## OPTIONS

Fax System 12

**Internet Fax Kit (A)**

**Printing System 16:** Fiery Controller

**Printing System Interface Kit 15:** Interface board for Fiery

### Paper handling

**PF-730(B) Paper feeder**

2x 500 sheets, 60 – 256 g/m<sup>2</sup>, A5R – 305 x 457 mm, folio

**PF-740(B) Paper feeder**

2x 1,500 sheets, 60 – 256 g/m<sup>2</sup>, A4, B5, letter

**PF-7130 Paper feeder**

500 sheets, 60 – 256 g/m<sup>2</sup>, A5R – 305 x 457 mm

**PF-7120 A4 side deck:** 3,000 sheets, 60 – 256 g/m<sup>2</sup>, A4, B5

**DF-7110 Document finisher**

Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730 attachment); max. 60 – 300 g/m<sup>2</sup>; max. B5R – 305 x 457 mm  
Sub-tray: 200 sheets A4; 60 – 300 g/m<sup>2</sup>; A6R – 305 x 457 mm  
Sub-tray (top): 100 sheets; 60 – 300 g/m<sup>2</sup>; A6R – A4  
Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5 – 305 x 457 mm

**PH-7C/PH-7D Punch unit for DF-7110**

2-hole/4-hole/Swedish type, 60 – 300 g/m<sup>2</sup>, A5R – A3

**MT-730(B) Mailbox sorter for DF-7110**

7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m<sup>2</sup>

**BF-730 Booklet and tri-folding unit for DF-7110**

Half folding: 60 – 256 g/m<sup>2</sup>, A3, B4, A4R

Booklet: max. 16 sheets (64 pages, 60 – 90 g/m<sup>2</sup>)

Non-staple folding: max. 5 sheets (60 – 90 g/m<sup>2</sup>)

Tri-folding: 60 – 105 g/m<sup>2</sup>, A4R; Multi tri-folding: 5 sheets

(60 – 90 g/m<sup>2</sup>), 3 sheets (91 – 105 g/m<sup>2</sup>)

**Copy tray (D):** upper tray 100 sheets, lower tray 250 sheets

### Banner Guide (A)

Banner paper feeding guide, up to 10 sheets

### Security

**Data Security Kit (E):** In line with ISO 15408 (Common Criteria) with security level EAL3

**USB IC Card Reader:** Card Authentication Kit (B)

**Keyboardholder 10**

**Numeric keypad:** NK-7100

**UG-33 AC:** ThinPrint support

**UG-34 AC:** Emulation (IBM Printer/EPSON LQ-850)

### Optional interface

**IB-35:** Direct Wi-Fi Interface

**IB-50:** Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT

**IB-51:** Wireless Lan Interface



KYOCERA Document Solutions Europe B.V. – Branch Office Germany  
Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany  
Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100  
www.kyoceradocumentsolutions.eu – info@deu.kyocera.com

KYOCERA Document Solutions Inc. – 2-28, 1-Chome – Tamatsukuri  
Chuo-Ku Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

YOUR KYOCERA BUSINESS PARTNER