

in MAXHUB.Global



MAXHUB_Global



► MAXHUB



MAXHUB

V5 Classic Series

C Series

LEGEND RETOLD

The Classic Series delivers intuitive interactions as well as outstanding sound and video performance. For both local meetings and teleconferences, participants may visualise their ideas instantly via updated audio & visual systems, giving the distant meeting attendees the feeling as if they were joining the session in person.



> 4k UHD Display

Low Parallax | Anti-glare 90% NTSC Wide color Gamut

> Seam Speakers

2.1 Stereo Sound 40W High-Power Speaker

> 12MP HDR Camera

Auto Framing Higher SNR

> Multiple Sizes

55/65/75/86 Inches Available

> Smart Writing

High-precision IR Touch Technology

3 Display Modes

Presentation | Standard Night Mode



USB Type-C Bridging the Divide



Multi-screen Interaction (up to 4 devices)



Optional Android 9.0/Windows 10



Auto Zoom In On the Speaker



6-element Microphone Array



Up to 8 metres Voice Pickup

> Specification

Specification	C55FA	C65FA	C75FA	C86FA
Display				
Size	55 inch	65 inch	75 inch	86 inch
Ratio	16:9	16:9	16:9	16:9
Resolution	3840×2160	3840×2160	3840×2160	3840×2160
Contrast Ratio	4500:1	4000:1	4000:1	4000:1
Viewing Angle	178° (H/V)	178° (H/V)	178° (H/V)	178° (H/V)
Colour Gamut	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Backlight Structure	DLED	DLED	DLED	DLED
Lifespan	≥30,000 hours	≥30,000 hours	≥30,000 hours	≥30,000 hours
Touch System				
Touch Principle	Infrared	Infrared	Infrared	Infrared
Touch Points	20 Points	20 Points	20 Points	20 Points
	Windows 10/Windows 8/	Windows 10/Windows 8/	Windows 10/Windows 8/	Windows 10/Windows 8/
Supported Systems	Windows 7/Windows XP/	Windows 7/Windows XP/	Windows 7/Windows XP/	Windows 7/Windows XP/
Supported Systems	Android/Linux/macOS X/Chrome	Android/Linux/macOS X/Chrome	Android/Linux/macOS X/Chrome	Android/Linux/macOS X/Chrome
Minimum Recognisable Object	2mm	2mm	2mm	2mm
Touch Object	Finger, Stylus	Finger, Stylus	Finger, Stylus	Finger, Stylus
Touch Accuracy	±1mm	±1mm	±1mm	±1mm
Writing Height	≤2mm	≤2mm	≤2mm	≤2mm
Touch Resolution	32768(W)×32768(D)	32768(W)×32768(D)	32768(W)×32768(D)	32768(W)×32768(D)
Speakers	. , , , , ,			, , , , ,
Channel	2.1	2.1	2.1	2.1
Power	2×10W+20W	2×10W+20W	2×10W+20W	2×10W+20W
Microphone				
Quantity	6	6	6	6
Voice Pickup Range	Up to 8m	Up to 8m	Up to 8m	Up to 8m
Camera	OP 10 0111	op to dill	op to dill	Sp to 6111
Quantity	1	1	1	1
Pixels	12MP	12MP	12MP	12MP
Location	In the Middle of the Upper Bezel			
I/O Ports				
HDMI IN	1	1	1	1
USB 2.0	1	1	1	1
USB 3.0	2	2	2	2
USB Type-C	2	2	2	2
TOUCH	1	1	1	1
AUDIO OUT	1	1	1	1
RS232	1	1	1	1
Compatible Modules*				
PC Module	MT51 (Windows 10)	MT51 (Windows 10)	MT51 (Windows 10)	MT51 (Windows 10)
Android Module	SA08 (Android 9.0)	SA08 (Android 9.0)	SA08 (Android 9.0)	SA08 (Android 9.0)
Accessories				5.135 (
Power Cable	×1	×1	×1	×1
Stylus	×2	×2	×2	×2
Wall Mount	×1	×1	×1	×1
Wi-Fi Module	×1	×1	×1	×1
Environment	***			~1
Operation Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C
Operation Humidity	10% to 90%RH	10% to 90%RH	10% to 90%RH	10% to 90%RH
, ,				
Storage Temperature	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C 10% to 90%RH	-20°C to 60°C
Storage Humidity	10% to 90%RH	10% to 90%RH		10% to 90%RH
Altitude	≤5000 metres	≤5000 metres	≤5000 metres	≤5000 metres





