JTOUCH SERIES 40 - INF6540E





Total Touch Control™

With 4K resolution, Total Touch Control[™], built-in education features, and an open Android platform, the JTouch INF6540e is a fully customizable, all-in-one teaching, collaboration, and presentation solution.

SkyBond manufacturing process provides Improved touch performance reducing the parallax to improve usability to a near "pen on paper" experience.

Features & Benefits

SkyBond Engineered for Intuitive Touch

This manufacturing process is designed to improve touch performance by reducing the parallax, improving usability to a near-"pen on paper" experience. 5th-generation infrared touch with 20 touch points helps make it easy to quickly pull up menu options with intuitive touch gestures and allows multiple users to engage simultaneously.

High Brightness Design

The JTouch helps you get your message across and connect with your audience with its 450 cd/m² of brightness, providing enhanced color and clarity. Combined with its 4K UHD native resolution, your images, text, and video will be seen in spaces with high ambient light.

Open Android Platform

Expand and customize the platform with nearly any Android application or game. Just download and install the application you want that's designed for interactive displays.

Interactive Whiteboard Functionality

Brainstorm, capture, save, and share your ideas on an interactive whiteboard with virtually no borders or barriers. Use a collection of digital pens, shapes, lines, and colors to create and draw on a multi-screen canvas. Paste backgrounds and images onto a whiteboard, annotate on top, and save it for the future. Intel Core™ i7-10700, 16GB Memory, 512GB SSD, Intel UHD Graphics 630

Annotation of Inputs

Capture the moment and add comments and diagrams to images from all connected inputs. Save these to the whiteboard or as a picture for future use with the quick annotation menu tool.

Included Wi-Fi Adapter & Optional Computer Module

With the included wireless adapter installed, participants can connect and share content securely from Windows and Mac computers, tablets, and smartphones to enhance collaboration and productivity in meetings. Add an optional computer module to expand the display's performance and software capabilities.

Display

JTouch Interactive Touch Display INF6540e | InFocus.com

In meracuve Touch Display maroj40e mrocus.com	
Screen Size (Diagonal)	65"
Backlight	D-LED
Native Resolution	4K
Pixels	3840 x 2160
Aspect Ratio	16:9
Contrast Ratio	1200:1
Dynamic Contrast Ratio	5000:1
Brightness (Maximum cd/m2)	450
Response Time (ms)	8
Display Colours (billion)	1.07
Refresh Rate (Hz)	60
Viewing Angle (H-V°)	178 / 178
Viewable Area (mm / in)	1428 x 804 / 56 x 32
Glass Treatment (mohs)	Antiglare, 7
Glass Thickness (mm)	3.2
Sensors	Light
Audio (w)	2 x 20
Lifetime Maximum (hrs)	50000
Frame Material	Aluminium

Connectivity

Inputs	
Mini D-sub 15-pin (VGA)	\checkmark
HDMI™ 2.0	\checkmark
HDMI [™] 2.0 with ARC	\checkmark
USB-A 2.0	\checkmark
USB-A 3.0	$\checkmark\checkmark\checkmark\checkmark\checkmark$
USB-C	\checkmark
USB-B	$\checkmark\checkmark$
3.5 mm Stereo Mini Jack	\checkmark
RJ45 - Lan 10/100/1000	\checkmark
Outputs	
3.5 mm Stereo Mini Jack	\checkmark
SPDIF	\checkmark
HDMI™ 2.0	\checkmark
RJ45 - Lan 10/100/1000	\checkmark
Other	
Wi-Fi 802.11a,n,ac,ax	\checkmark
Bluetooth 2.1, 3, 4, 4.1, 4.2, 5	\checkmark
Open Pluggable Specification (OPS) Slot	

Power

Power Supply (V / Hz)	AC 100 - 240, 50/60
Power Consumption Max[W]	450
Power Consumption Network Standby (W)	<2.0
Power Consumption Standby (W)	<0.5

JTouch Interactive Touch Display INF6540e | InFocus.com

Touch System

Touch Technology	IR
Touch Points Maximum	40
Typical Response Time (ms)	<10
Accuracy (mm)	+/- 1
Minimum Object Size Single Touch (mm)	>3
Minimum Object Size Multi Touch (mm)	>8
Supported Operating Systems	Windows, Linux, Mac OS, Chrome

Embedded System

Operating System & Version	Android 9
System on Chip (SoC)	MT9950 (S900) 8K
Central Processing Unit (CPU)	ARM Cortex™ A73 Quad Core 1.8Ghz
Graphics Processing Unit (GPU)	ARM Mail G52 MC2
Random Access Memory (RAM)	4
Read Only Memory (ROM)	32
	Whiteboard, Browser, Finder, LightCast3, Annotation, WPS Office,
Included Applications	Stopwatch, Screen Capture, LightServer, LightManager, LightStore, Palette, Keeper, Visulizer, Welcome, Cloud Drive, SpotLight, Screen

Recording, Timer,

Optional Upgrades

Intel® Core™ i5 10th Gen Slot-In PC	PC-I5-10400-8256
Intel® Core™ i7 10th Gen Slot-In PC	PC-I7-10700-16256

General

Dimensions (W x H x D) [mm / in]	1488 x 86 x 897 / 58.9 x 3.4 x 35.1
Weight [kg / lb]	38.0 / 83.8
Shipping Dimensions (W x H x D) [mm / in]	1628 x 208 x 1005 / 64.1 x 8.2 x 39.6
Shipping Weight [kg / lb]	48.5 / 106.9
Mounting VESA MIS-F	600 x 400
Operating Temperature [°C / F]	0 ~ 40 / 32 ~104
Operating Humidity [%]	10 ~ 90
Operating Altitude (m / ft)	<5000 / >16404
Storage Temperature [°C / F]	-20 ~ 60 / -4 ~140
Storage Humidity [%]	10 ~ 90
Security	PIN, Kensington Lock
In the Box	Remote Control (no batteries), 2x Sylus, Power Cord, 3m USB A to B, 3m HDMI, QSG, WiFI Module
Safety and Regulatory	CB, CE EMC, IC, FCC, cTUVus, NOM, EAC, BIS
Environmental	RoHS, WEEE, EU Energy

Copyright © 2022, InFocus and its logo is a registered trademark of InFocus Corporation. Maxnerva Technology Services Limited is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted; all specifications are subject to change without notice. All images are for representation purposes only and may be simulated.