

Specifications

	e-STUDIO3025AC/3525AC/4525AC	e-STUDIO5525AC/6525AC
General		
Print & Copy Speed	A4: 30 / 35 / 45 ppm	A4: 55 / 65 ppm
	A3: 16 / 18 / 22 ppm	A3: 27 / 30 ppm
Warm-up Time ~	12 seconds from low power mode	20 seconds from low power mode
Paper Size & Weight	Drawer 1 : A5R-A3, 60-300 g/m²	
	Drawer 2: A5R-A3 / A5R-320 x 460 mm, 60-300 g/m²	
	Bypass: Single Feed: 100 x 148 mm-A3, 52-300 g/m²	
	Banner paper (up to 305 x 1,200 mm, 90-163 g/m²)	
Paper Capacity	Drawer : 2 x 550 sheets	
	Bypass: 1 x 100 sheets	
	Max. 5,200 sheets	
Automatic Duplex	A5R-A3, 60-256 g/m²	
Controller Type	Toshiba e-BRIDGE Next	
Control Panel	26 cm (10.1") Multi-Touch Colour Panel	
Memory	4 GB	6 GB
Security SSD (Standard/Max)	128 GB / 640 GB	
Interface	10Base-T/100Base-TX/1000Base-T, High Speed, USB 2.0, WLAN* (IEEE802.11a/b/g/n/ac), Bluetooth*, Wi-Fi Direct	
Dimension & Weight	585 x 641 x 787 mm (W x D x H), ~77kg	585 x 641 x 787 mm (W x D x H), ~79 kg
Print		
Resolution	600 dpi x 600 dpi, 5bit. PS Driver: 1200 dpi x 1200 dpi & 3,600 (Equivalence) x 1200 dpi	
Page Description Language	PCL5e, PCL5c, PCL6 (PCL XL), XPS, PDF and PS3, JPEG	
Supported Systems	Windows 11/10/8.1, Windows Server2022/2019/2016/2012 R2/2012 (64bit), Mac OS 10.12-12, Linux/Unix, Citrix, SAP, AS/400	
Network Protocols	TCP/IP (IPv4/IPv6, NetBios over TCP/IP)	
Mobile Printing	e-BRIDGE Print & Capture, Mopria® Print Service, AirPrint on iOS or macOS®	
Print Functions	Universal Printer Driver, Driver Templates, Driver plug-ins*, Print from USB, Hold Print, Tandem Printing, E-Mail direct printing	
Scan		
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi	
Scan Speed	Reversing Automatic Document Feeder*: up to 73 ipm (300 dpi) in colour and monochrome Dual Scan Document Feeder*: up to 240 ipm (300 dpi) in colour and monochrome	
Scan Modes	Auto-Colour (ACS), Colour, Greyscale, Monochrome	
File Formats	"JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, PDF/A, PDF/A-2, Searchable PDF* (and other formats like DOCX, XLSX, PPTX)*"	
Scan Functions	"WS Scan, Scan to USB, Scan to E-Mail, Scan to File, (SMB, FTP, FTPS, IPX/SPX, Local), Meta Scan*, OCR scan, Scan to Box (e-Filing), WIA, TWAIN"	
Copy		
Resolution Scan:	600 x 600 dpi	
Print: equiv.	2,400 x 600 dpi (with smoothing) (mono)	600 x 600 dpi 5bit (colour)
First Copy Output Time	(30 & 35 ppm) 5.9 sec. (mono) / 7.8 sec. (colour) (45 ppm) 4.4 sec. (mono) / 5.7 sec. (colour)	(55 & 65 ppm) 4.3sec. (mono) / 5.6 sec. (colour)
Multiple Copying	Up to 999 copies	
Copy Modes	Text/Photo, Text, Photo, Custom	
Copy Functions	Electronic Sort, Rotate Sort, ID Card Copy, Edge Erase, 2-in-1 / 4-in-1 mode	
FAX		
Communication	Super G3, G3 - (opt. 2nd line) Internet Fax T.37	
Transmission Speed	3 seconds per page	
Compression	JBIG, MMR, MR, MH	
Fax Memory	1 GB Transmission/Reception	
Network-Fax	Driver for Windows 11/10/8.1, Windows Server2022/2019/2016/Server 2012 R2/Server 2012 (64bit)	
Incoming Fax Routing	To shared folders (SMB, FTP), E-Mail, e-Filing	
System & Security		
Device Management	e-BRIDGE CloudConnect (eCC) & Top Access for remote administrations & configurations	
System Features	"e-Filing document server for secure storage, Document distribution and Print-on-Demand (one public box, 200 user boxes), 12,060 one-touch templates for storage of personalised settings and workflows, Scan/Fax Preview, Rip-while-Print, e-BRIDGE Open Platform, Embedded Web Browser, Job Skip, PCL Barcode printing, e-BRIDGE Plus Embedded Apps"	
Accounting & Security	"Role Based Access, LDAP support, 1,000 department & 10,000 user codes, Card Reader*, Private Print, Scan to Secure PDF, Pull-printing* Standard data encryption with Security SSD, Data Overwrite function when optional HDD is chosen, IP and MAC address filter, Port Filter, Support of SSL and IPsec* protocols, IEEE802.1 x support, CC certified (ISO/IEC15408) with HCD-PP v1.0"	